TOYOTA TUNDRA CREWMAX/DOUBLE CAB 2022-CURRENT NON-HYBRID MODELS

LOCKING UNDER SEAT STORAGE

PART# USSCM-04

KΙΊ	$\boldsymbol{\Gamma}$	\sim 10	uт		NI٦	rc.
NI	L	Uľ	VІ	CI	N I	rs:

UNDER SEAT STORAGE ASSEMBLY WITH KEYS

HARDWARE BAG WITH 10 %-20 HEX TAMPER PROOF SCREWS, 10 %-20 JACKNUTS AND WRENCH

INSTALLATION INSTRUCTIONS

	_			_
$T \cap \cap C$	REQUIRED		TAII	$\Delta TI \cap NI$.
LUULS	REUUIRED	FUR IIVS	IALL	AIICIN:

14MM SOCKET, 10MM SOCKET AND RATCHET

5/32 HEX HEAD SECURITY BIT(AVAILABLE ON AMAZON)

29/64THS DRILL BIT AND DRILL

FLAT HEAD SCREWDRIVER OR CLIP REMOVER

PLIERS

SAFETY GLASSES

PROTECTIVE BLANKET

WARNING!

Installing this product in your

Vehicle requires the use of sharp objects.

Please make sure you use the proper tools and use them in a safe manner.

We are not responsible for injuries incurred while installing this product.



2022-CURRENT TOYOTA TUNDRA CREWMAX/DOUBLE CAB NON-HYBRID

LOCKING UNDER SEAT STORAGE

INSTALLATION INSTRUCTIONS

- 1. REMOVE ALL CONTENTS FROM BOX
- 2. LIFT BOTH SIDES OF REAR SEAT
- 3. LOCATE THE 4 14MM BOLTS SECURING THE SEATS AND REMOVE. YOU WILL NEED TO RELEASE THE CENTER SEAT BELT SHOULDER BELT BY USING THE BUCKLE AND INSERT IT INTO THE SIDE SLOT OF THE SEAT BELT FEMALE PORTION TO RELEASE THE STRAP.
- 4. PULL SEAT BACK LATCH TO RELEASE THE REAR SEATS FROM THE BACK WALL OF THE TRUCK AND REMOVE SEATS. PLACE SEATS ON A PROTECTIVE BLANKET TO KEEP DAMAGE FROM THE SEATS.
- 5. REMOVE REAR DOOR SILL PLATES
- 6. LOOKING AT THE TRIM AROUND THE FACTORY UNDER SEAT STORAGE, LOCATE THE 10 PUSH PIN RETAINING CLIPS. USING A SMALL FLATHEAD SCREWDRIVER, PUSH IN ON THE CENTER OF THE CLIP TO RELEASE, AND REMOVE ALL 10 CLIPS.
- 7. ONCE CLIPS ARE REMOVED, REMOVE CENTER TRIM PANEL BY PULLING FROM THE BOTTOM OF ONE SIDE TO RELEASE RETAINING CLIPS. ONCE REMOVED PULL THE SIDE TRIM PANELS TOWARDS THE FRONT SEATS TO RELEASE RETAING CLIPS. SET ALL TRIM PANELS ASIDE AND PROTECT AS TO NOT SCRATCH PANELS.
- 8. USING A 14MM SOCKET, REMOVE THE 4 SEAT BELT FEMALE RECEPTICLES. THEY WILL HAVE WIRES, SO JUST SET THEM INSIDE THE PLASTIC STORAGE FOR NOW.
- 9. USING THE CLIP REMOVER, REMOVE THE 6 PLASTIC RETAINING CLIPS ON THE BACK WALL OF THE FACTORY STORAGE AND REMOVE THE BLACK PLASTIC PANEL.
- 10. REMOVE THE JACK AND TOOL STORAGE BAG AND SET ASIDE. USING A 10MM SOCKET, REMOVE THE TOOL STORAGE BAG RETAINING STRAP. REMOVE THE 10MM BOLT IN THE PANEL TO THE LEFT OF THE STRAP AS WELL AS THE ONE ON THE RIGHT SIDE OF THE PANEL.
- 11. REMOVE THE DRIVER SIDE REAR BACK WALL PANEL BY PULLING TO RELEASE THE RETAINING CLIPS, THEN REMOVE THE PASSENGER SIDE REAR BACK WALL PANEL.
- 12. LOCATE THE THREE CLIPS HOLDING THE WIRING HARNESS FOR THE REAR SEAT BELTS ATTACHED TO THE UNDERSIDE OF THE FACTORY STORAGE. THEY ARE CLIPPED FROM THE BOTTOM BUT CAN BE RELEASED FROM THE TOP SIDE OF THE STORAGE. USING PLIERS, SQUEEZE EITHER THE SIDES OR THE ENDS OF THE CLIPS AND PRESS THEM THROUGH THE STORAGE.

- 13. AT THIS POINT, THERE IS ONE CLIP LEFT ON THE FRONT EDGE OF THE STORAGE. REMOVE AND DISCARD THIS CLIP. REMOVE THE FACTORY STORAGE BOX BY PULLING UP ON THE FRONT EDGE OF THE STORAGE AND PULL OUT.
- 14. USING A 29/64THS DRILL BIT, DRILL OUT THE 10 HOLES THE PUSH PIN RETAINING CLIPS WERE IN. IT IS NOT NECESSARY TO DRILL OUT THE ONE IN THE CENTER AS THIS WILL NOT BE USED.
- 15. INSTALL A ½-20 JACKNUT INTO EACH OF THE HOLES DRILLED. USING THE JACK NUT WRENCH AND SUPPLIED ½-20 SCREW, INSERT THE SCREW THROUGH THE WRENCH AND INTO THE JACKNUT AND TIGHTEN DOWN UNTIL THE JACKNUT IS TIGHT IN THE HOLE. DO NOT UNDER TIGHTEN AS THIS WILL CAUSE THE JACK NUT TO SPIN.
- 16. ONCE ALL OF THE JACK NUTS ARE IN AND TIGHT, PLACE ESP STORAGE INTO PLACE.
- 17. AT THIS POINT, REINSTALL THE TWO SIDE STORAGE TRIM PANELS AND CENTER TRIM PANEL.
- 18. LINE UP THE HOLES IN THE STORAGE AND INSTALL THE 10 ¼-20 TAMPER PROOF SECURITY SCREWS. ONCE ALL 10 SCREWS ARE IN, TIGHTEN THEM DOWN USING THE SECURITY BIT.
- 19. PERFORM STEPS 8-11 IN THE REVERSE ORDER.
- 20. REINSTALL REAR SEATS
- 21. REINSTALL DOOR SILL PANELS.

HERE IS A LINK TO THE INSTALLATION VIDEO ON OUR YOUTUBE CHANNEL https://youtu.be/v50sxyDN9Vs OR JUST SEARCH ESP Under Seat Lockable Storage for 2022-Current Tundra CrewMax & Double Cab (Non Hybrid) Install

THANK YOU FOR YOUR PURCHASE. IF YOU HAVE ANY QUESTIONS AT ALL ON THE INSTALL, PLEASE CALL EARL AT 951-858-3418 8AM TO 7PM PACIFIC TIME. IF NO ANSWER, LEAVE A MESSAGE AND I WILL CALL WHEN AVAILABLE. YOU CAN TEXT AS WELL